HEC-160SA-4FX

Technical details

Flex ATX - power supplies are suitable for mini-ATX based PC systems because of their small size and they work at at very low noise level.

Features:

- High efficiency (67% minimum, 72% typical at full load)
- full range active PFC 110V-230V
- TC (Thermal Control) Function / Fan control
- 100% Hi-pot & Function (Chroma) tested
- Silent technology (<32dB At Full Load)
- 100% burn-in high ambient temperature under (50 ° C)
- MTBF 100,000 hours at 25 ° C
- CB, TUV, CE, FCC certified
- OPP / OVP / SCP

HEC-160SA-4FX

Specifications

Model	HEC-120SA-7FX	HEC-160SA-4FX	HEC-200SA-2FX

Output	Max	Max Comb Power	Max	Max Comb Power	Max	Max Comb Power
+3.3V	10A	50 Watts	16.7A	61 Watts	16.7A	80 Watts
+5V	10A		12A		13A	
+12V	9.5A	115 Watts	10A	120 Watts	14A	
-12V	0.3A	3.6 Watts	0.3A		0.3A	
+5Vsb	2A	10 Watts	2 A		1.5A	
Total Power	**120 Watts**		**160 Watts**		**200 Watts**	

Model	HEC-120SA-7FX	HEC-160SA-4FX	HEC-200SA-2FX
24 (20+4) Pin Mainboard	1	1	1
4 Pin 12V	1	1	1
4 Pin P-ATA	2	2	2
S-ATA	1	1	1
FDD	1	1	1